

200W CPC semi-flexible solar panel

Warranty

- ◆ 2 years Manufacturer Warranty

Manufacturing

- ◆ Original cell sorting system ensures the best electric cell match
- ◆ EL-Testing before packing.
- ◆ Comprehensive module power testing.

Performance

- ◆ Upgraded efficiency and unprecedented flexibility.
- ◆ Weakened hot-spot effect, extremely low risk of micro cracks and increased stability by shingle-tech.
- ◆ Special connection method lowers the internal resistance and ensures better performance than traditional connection with busbar.
- ◆ IP67 rated junction box, reliable cables and standard MC4 connectors improve the stability



Mechanical Data

Standard Test Conditions AM=1.5, E=1000W/m², TC=25°C

Nominal Power	200W
Cell Type	Monocrystalline
Model of Cells	182mm
Maximum Power Current (Impp)	9.62A
Maximum Power Voltage (Vmpp)	20.88V
Open-circuit Voltage (Voc)	24.48V
Short-circuit Current (Isc)	10.19A
Maximum System Voltage	100V
Output Tolerance	±3%
Cable	900mm / 2.5mm ²
Connector Type	MC4 / MC4 Compatible
Module Structure	CPC/EVA / Backsheet
Junction box rating	≥ IP67
Diode	✓
Working Temperature	-20°C~+65°C

Packaging

Module Dimensions	1295*780*2mm
Module Weight	4.2kg
Package	Single Package
Pieces per Pallet	30
Gross Weight per Pallet	210
Pallet Dimensions	1310*1100*950mm



LLUMOR

PASIÓN POR LA EFICIENCIA ENERGÉTICA

ES 25710 CASTELLCIUTAT / Lleida, Ctra. N-260, N°18
+34 073355540 | +34 619770556

info@llumor.es | www.llumor.es

